

Features

- Ideal for indication light on hand held products
- Long life and robust package
- Standard Package: 500 pcs / Reel
- MSL (Moisture Sensitivity Level): 3
- AEC-Q102 Qualified
- Halogen-free
- RoHS compliant




ATTENTION
OBSERVE PRECAUTIONS
FOR HANDLING
ELECTROSTATIC
DISCHARGE
SENSITIVE
DEVICES

Applications

- Backlighting for tell-tale indicators
- Dashboard lighting
- Interior lighting (footwell, dome light, accent lighting, etc.)
- Signs and signals
- Various applications requiring high temperature rating

Package Schematics



Notes:

1. All dimensions are in millimeters (inches).
2. Tolerance is $\pm 0.2(0.008)$ unless otherwise noted.
3. Specifications are subject to change without notice.

Part Number	Emitting Color (Material)	Lens-color	Luminous Intensity CIE127-2007* (If=20mA) mcd			Viewing Angle [1]
			Code.	Min.	Max.	
XZDG79W-HTAQ	Green (InGaN)	Water Clear	Z*	2700*	3100*	2 θ 1/2 60°(H) 35°(V)
			ZA*	3100*	3600*	
			ZB*	3600*	4200*	
			ZC*	4200*	5000*	
			ZD*	5000*	6000*	
			ZE*	6000*	7000*	

Notes:

1. θ1/2 is the angle from optical centerline where the luminous intensity is 1/2 of the optical peak value.

* Luminous intensity value is in accordance with CIE127-2007 standards.

2. Listed bin codes represent the possible range for this LED. Actual bin codes received will be based upon production yields.

Electrical / Optical Characteristics at Ta=25°C

Parameter	Symbol	Value				Unit
		Code.	Min.	Typ.	Max.	
Wavelength at Peak Emission CIE127-2007* If = 20mA	λpeak	-	-	520*	-	nm
Dominant Wavelength CIE127-2007* If = 20mA	λdom [1]	1*	515*	-	520*	nm
		2*	520*	-	525*	
		3*	525*	-	530*	
		4*	530*	-	535*	
Spectral Bandwidth at 50%Φ REL MAX If = 20mA	Δλ	-	-	35	-	nm
Forward Voltage If = 20mA	VF [2]	-	-	2.8	3.5	V
Reverse Current (VR = 5V)	IR	-	-	-	50	μA
Temperature Coefficient of λpeak If = 20mA, -10°C ≤ T ≤ 100°C	TCλpeak	-	-	0.04	-	nm/°C
Temperature Coefficient of λdom If = 20mA, -10°C ≤ T ≤ 100°C	TCλdom	-	-	0.04	-	nm/°C
Temperature Coefficient of VF If = 20mA, -10°C ≤ T ≤ 100°C	TCV	-	-	-2.5	-	mV/°C

Notes:

1. Wavelength : + / -1nm.

2. Forward Voltage: +/-0.1V.

* Wavelength value is traceable to CIE127-2007 standards.



3. Listed bin codes represent the possible range for this LED. Actual bin codes received will be based upon production yields.

Absolute Maximum Ratings at Ta=25°C





Parameter	Symbol	Value	Unit
Power Dissipation	P _D	70	mW
Reverse Voltage	V _R	5	V
Junction Temperature	T _j	115	°C
Operating Temperature	T _{op}	-40 ~ +100	°C
Storage Temperature	T _{stg}	-40 ~ +110	°C
DC Forward Current	I _F	20	mA
Electrostatic Discharge Threshold (HBM)		2000	V
Peak Forward Current [2]	I _{FP}	100	mA
Thermal Resistance (Junction/Ambient) [1]	R _{th j-a}	560	°C/W
Thermal Resistance (Junction/Solder point) [1]	R _{th j-s}	440	°C/W

Notes:

1. R_{th(j-a)}, R_{th(j-s)} Results from mounting on PC board FR4 (pad size ≥ 16 mm² per pad).
2. 1/10 Duty Cycle, 0.1ms Pulse Width.
3. A Relative Humidity between 40% and 60% is recommended in ESD-protected work areas to reduce static build up during assembly process (Reference JEDEC/JESD625-A and JEDEC/J-STD-033).




❖ Green



- ❖ LED is recommended for reflow soldering and soldering profile is shown below.


Reflow Soldering Profile for SMD Products (Pb-Free Components)




Notes:

1. All temperatures refer to the center of the package, measured on the package body surface facing up during reflow.
2. Do not apply any stress to the LED during high temperature conditions.
3. Maximum number of soldering passes: 2

- ❖ The device has a single mounting surface. The device must be mounted according to the specifications.





- ❖ Reel Dimension (Units : mm)




- ❖ Recommended Soldering Pattern (Units : mm; Tolerance: ± 0.1)

Pad design for improved heat dissipation



- ❖ Tape Specification (Units : mm)





Remarks:

If special sorting is required (e.g. binning based on forward voltage, luminous intensity / luminous flux, or wavelength), the typical accuracy of the sorting process is as follows:

1. Wavelength: +/-1nm
2. Luminous Intensity / Luminous Flux: +/-15%
3. Forward Voltage: +/-0.1V

Note: Accuracy may depend on the sorting parameters.

Packing & Label Specifications



TERMS OF USE

1. Data presented in this document reflect statistical figures and should be treated as technical reference only.
2. Contents within this document are subject to improvement and enhancement changes without notice.
3. The product(s) in this document are designed to be operated within the electrical and environmental specifications indicated on the datasheet. User accepts full risk and responsibility when operating the product(s) beyond their intended specifications.
4. The product(s) described in this document are intended for electronic applications in which a person's life is not reliant upon the LED. Please consult with a SunLED representative for special applications where the LED may have a direct impact on a person's life.
5. The performance of the product(s) should be evaluated and verified by the customer to ensure it can meet the customer's application requirements.
6. The contents within this document may not be altered without prior consent by SunLED.
7. Additional technical notes are available at <https://www.SunLEDusa.com/TechnicalNotes.asp>